

Functions and Abstraction


BBM 101 - Introduction to Programming I

Hacettepe University
Fall 2015

Fuat Akal, Aykut Erdem, Erkut Erdem, Vahid Garousi

Functions

- In math, you **use** functions: sine, cosine, ...
- In math, you **define** functions: $f(x) = x^2 + 2x + 1$



- A function packages up and names a computation
 - Enables re-use of the computation (generalization)
 - **Don't Repeat Yourself** (DRY principle)
 - Shorter, easier to understand, less error-prone
-
- Python lets you **use** and **define** functions
 - We have already seen some Python functions:
 - `len`, `float`, `int`, `str`, `range`

Using (“calling”) a Function

`len("hello")`

`len("")`

`round(2.718)`

`round(3.14)`

`pow(2, 3)`

`range(1, 5)`



`math.sin(0)`

`math.sin(math.pi / 2)`

- Some need no input: `random.random()`
- All produce output

A Function is a Machine


- You give it input
- It produces a result (output)



In math: $\text{func}(x) = 2x + 1$

Creating a Function

Define the machine,
including the input and the result



More Function Examples

Define the machine, including the input and the result

```
def square(x):  
    return x * x  
  
def fahr_to_cent(fahr):  
    return (fahr - 32) / 9.0 * 5  
  
def cent_to_fahr(cent):  
    result = cent / 5.0 * 9 + 32  
    return result  
  
def abs(x):  
    if x < 0:  
        return -x  
    else:  
        return x
```

```
def print_hello():  
    print "Hello, world"
```

No return statement
Returns the value None
Are also called 'procedures'

```
def print_fahr_to_cent(fahr):  
    result = fahr_to_cent(fahr)  
    print result
```


What is the result of:

```
x = 42  
square(3) + square(4)  
print x  
boiling = fahr_to_cent(212)  
cold = cent_to_fahr(-40)  
Print(result)  
print(abs(-22))  
print(print_fahr_to_cent(32))
```

Python Interpreter

- An expression evaluates to a value
 - Which can be used by the containing expression or statement
- `print("test")` statement writes text to the screen
- The Python interpreter (command shell) reads statements and expressions, then executes them
- If the interpreter executes an expression, it prints its value
- In a program, evaluating an expression does not print it
- In a program, printing an expression does not permit it to be used elsewhere

How Python Executes a Function Call



1. Evaluate the **argument** (at the call site)
2. Assign the **formal parameter name** to the argument's value
 - A *new* variable, not reuse of any existing variable of the same name
3. Evaluate the **statements** in the body one by one
4. At a **return** statement:
 - Remember the value of the expression
 - Formal parameter variable disappears – exists only during the call!
 - The call expression evaluates to the return value

Example of Function Invocation

```
def square(x):  
    return x * x  
  
square(3) + square(4)  
return x * x  
return 3 * x  
return 3 * 3  
return 9  
  
9 + square(4)  
    return x * x  
    return 4 * x  
    return 4 * 4  
    return 16  
  
9 + 16  
25
```

Variables:

(none)	
(none)	x: 4
(none)	
(none)	

Expression with Nested Function Invocations: Only One Executes at a Time

```
def fahr_to_cent(fahr):  
    return (fahr - 32) / 9.0 * 5
```

```
def cent_to_fahr(cent):  
    return cent / 5.0 * 9 + 32
```

```
fahr_to_cent(cent_to_fahr(20))  
    return cent / 5.0 * 9 + 32  
    return 20 / 5.0 * 9 + 32  
    return 68
```

```
fahr_to_cent(68)  
return (fahr - 32) / 9.0 * 5  
return (68 - 32) / 9.0 * 5  
return 20
```

20

Variables:

(none)

cent: 20

cent: 20

cent: 20

(none)

fahr: 68

fahr: 68

fahr: 68

(none)

Expression with Nested Function Invocations: Only One Executes at a Time

```
def square(x):  
    return x * x  
  
square(square(3))  
    return x * x  
    return 3 * x  
    return 3 * 3  
    return 9  
  
square(9)  
    return x * x  
    return 9 * x  
    return 9 * 9  
    return 81
```

Variables:

(none)

(none)

(none)

81

Function that Invokes Another Function: Both Function Invocations are Active

```
def square(z):  
    return z*z  
  
def hypoten_use(x, y):  
    return math.sqrt(square(x) + square(y))
```

```
Hypoten_use(3, 4)
```

```
    return math.sqrt(square(x) + square(y))
```

Variables:

(none)

y:4

```
    return math.sqrt(square(3) + square(y))
```

y:4

```
    return z*z
```

z: 3 y:4

```
    return 3*3
```

z: 3 y:4

```
    return 9
```

z: 3 y:4

```
    return math.sqrt(9 + square(y))
```

y:4

```
    return math.sqrt(9 + square(4))
```

y:4

```
    return z*z
```

z: 4 y:4

```
    return 4*4
```

z: 4 y:4

```
    return 16
```

z: 4 y:4

```
    return math.sqrt(9 + 16)
```

y:4

```
    return math.sqrt(25)
```

y:4

```
    return 5
```

y:4

(none)

Shadowing of Formal Variable Names

```
def square(x):  
    return x*x  
  
def hypotenuse(x, y):  
    return math.sqrt(square(x) + square(y))  
  
hypotenuse(3, 4)  
    return math.sqrt(square(x) + square(y))  
    return math.sqrt(square(3) + square(y))  
    return x*x  
    return 3*3  
    return 9  
    return math.sqrt(9 + square(y))  
    return math.sqrt(9 + square(4))  
    return x*x  
    return 4*4  
    return 16  
    return math.sqrt(9 + 16)  
    return math.sqrt(25)  
    return 5
```

Same formal parameter name

Variables:

(none)

y:4

y:4

y:4

y:4

y:4

y:4

x: 4 y:4

x: 4 y:4

x: 4 y:4

y:4

y:4

y:4

Formal parameter is a new variable

Shadowing of Formal Variable Names


```
def square(x) :
    return x*x

def hypotenuse(x, y) :
    return math.sqrt(square(x) + square(y))

hypotenuse(3, 4)
    return math.sqrt(square(x) + square(y))
    return math.sqrt(square(3) + square(y))
        return x*x
        return 3*3
        return 9
    return math.sqrt(9 + square(y))
    return math.sqrt(9 + square(4))
        return x*x
        return 4*4
        return 16
    return math.sqrt(9 + 16)
    return math.sqrt(25)
return 5
```

Same diagram, with
variable scopes or
environment frames
shown explicitly

Variables:



In a Function Body, Assignment Creates a Temporary Variable (like the formal parameter)

```
stored = 0  
  
def store_it(arg):  
    stored = arg  
    return stored
```

- ★ `y = store_it(22)`
- `print y`
- ★ `print stored`

Show evaluation of the starred expressions:

```
y = store_it(22)  
    stored = arg; return stored  
    stored = 22; return stored  
    return stored  
    return 22  
  
y = 22  
print stored  
print 0
```

Variables:

Global or
top level

store_it()
arg: 22
arg: 22
arg: 22 stored: 22
arg: 22 stored: 22

stored: 0
stored: 0
stored: 0
stored: 0
stored: 0 y: 22
stored: 0 y: 22
stored: 0 y: 22

How to Look Up a Variable

Idea: find the nearest variable of the given name

1. Check whether the variable is defined in the **local scope**
2. ... check any intermediate scopes (**none** in CSE 140!) ...
3. Check whether the variable is defined in the **global scope**

If a local and a global variable have the **same name**, the global variable is inaccessible ("**shadowed**")

This is confusing; try to avoid such shadowing

```
x = 22
stored = 100
def lookup():
    x = 42
    return stored + x
lookup()
x = 5
stored = 200
lookup()
```

```
def lookup():
    x = 42
    return stored + x
x = 22
stored = 100
lookup()
x = 5
stored = 200
lookup()
```

What happens if
we define **stored**
after **lookup**?

Local Variables Exist Only while the Function is Executing

```
def cent_to_fahr(cent):  
    result = cent / 5.0 * 9 + 32  
    return result  
  
tempf = cent_to_fahr(15)  
print result
```

Use Only the Local and the Global Scope

```
myvar = 1

def outer():
    myvar = 1000
    return inner()

def inner():
    return myvar

print outer()
```

The handouts have a more precise rule,
which applies when you define a function inside another function.

Abstraction



- Abstraction = ignore some details
- Generalization = become usable in more contexts
- Abstraction over **computations**:
 - functional abstraction, a.k.a. procedural abstraction
- As long as you know what the function **means**, you don't care **how** it computes that value
 - You don't care about the *implementation* (the function body)

Defining Absolute Value

```
def abs(x):  
    if val < 0:  
        return -1 * val  
    else:  
        return 1 * val  
  
def abs(x):  
    if val < 0:  
        return - val  
    else:  
        return val
```

```
def abs(x):  
    if val < 0:  
        result = - val  
    else:  
        result = val  
    return result  
  
def abs(x):  
    return math.sqrt(x*x)
```

Defining Round (for positive numbers)

```
def round(x):  
    return int(x+0.5)
```

```
def round(x):  
    fraction = x - int(x)  
    if fraction >= .5:  
        return int(x) + 1  
    else:  
        return int(x)
```

Two Types of Documentation

1. Documentation for **users/clients/callers**
 - Document the *purpose* or *meaning* or *abstraction* that the function represents
 - Tells **what** the function does
 - Should be written for *every* function
2. Documentation for **programmers** who are reading the code
 - Document the *implementation* – specific code choices
 - Tells **how** the function does it
 - Only necessary for tricky or interesting bits of the code

For **users**: a string as the first element of the function body

```
def square(x):  
    """Returns the square of its argument."""  
    # "x*x" can be more precise than "x**2"  
    return x*x
```

For **programmers**:
arbitrary text after #

Multi-line strings

- New way to write a string – surrounded by three quotes instead of just one
 - "hello"
 - 'hello'
 - """hello"""
 - '''hello'''
- Any of these works for a documentation string
- Triple-quote version:
 - can include newlines (carriage returns), so the string can span multiple lines
 - can include quotation marks

Don't write useless comments

- Comments should give information that is not apparent from the code
- Here is a counter-productive comment that merely clutters the code, which makes the code *harder* to read:

```
# increment the value of x  
x = x + 1
```

Where to write comments

- By convention, write a comment *above* the code that it describes (or, more rarely, on the same line)
 - First, a reader sees the English intuition or explanation, then the possibly-confusing code

```
# The following code is adapted from
# "Introduction to Algorithms", by Cormen et
al.,
# section 14.22.
while (n > i):
    ...
    ...
```
- A comment may appear anywhere in your program, including at the end of a line:

```
x = y + x      # a comment about this line
```
- For a line that starts with #, indentation must be consistent with surrounding code

Each variable should represent one thing

```
def atm_to_mbar(pressure):
    return pressure * 1013.25

def mbar_to_mmHg(pressure):
    return pressure * 0.75006

# Confusing
pressure = 1.2 # in atmospheres
pressure = atm_to_mbar(pressure)
pressure = mbar_to_mmHg(pressure)
print pressure

# Better
in_atm = 1.2
in_mbar = atm_to_mbar(in_atm)
in_mmHg = mbar_to_mmHg(in_mbar)
print in_mmHg
```

```
# Best
def atm_to_mmHg(pressure):
    in_mbar = atm_to_mbar(pressure)
    in_mmHg = mbar_to_mmHg(in_mbar)
    return in_mmHg
print atm_to_mmHg(1.2)
```

Corollary: Each variable should contain values of only one type

```
# Legal, but confusing: don't do this!
x = 3
...
x = "hello"
...
x = [3, 1, 4, 1, 5]
...
```

If you use a descriptive variable name, you are unlikely to make these mistakes

Exercises

```
def cent_to_fahr(c):
    print cent / 5.0 * 9 + 32

print cent_to_fahr(20)
```

```
def myfunc(n):
    total = 0
    for i in range(n):
        total = total + i
    return total

print myfunc(4)
```

```
def c_to_f(c):
    print "c_to_f"
    return c / 5.0 * 9 + 32
```

```
def make_message(temp):
    print "make_message"
    return ("The temperature is "
+ str(temp))

for tempc in [-40,0,37]:
    tempf = c_to_f(tempc)
    message = make_message(tempf)
    print message
```

double(7)

abs(-20 - 2) + 20

Use the Python Tutor:
<http://pythontutor.com>

What does this print?

```
def cent_to_fahr(cent):  
    print cent / 5.0 * 9 + 32  
  
print cent_to_fahr(20)
```

What does this print?

```
def myfunc(n) :  
    total = 0  
    for i in range(n) :  
        total = total + i  
    return total  
  
print myfunc(4)
```

What does this print?

```
def c_to_f(c):
    print "c_to_f"
    return c / 5.0 * 9 + 32

def make_message(temp):
    print "make_message"
    return "The temperature is " + str(temp)

for tempc in [-40,0,37]:
    tempf = c_to_f(tempc)
    message = make_message(tempf)
    print message
```

c_to_f
make_message
The temperature is -40.0
c_to_f
make_message
The temperature is 32.0
c_to_f
make_message
The temperature is 98.6

Decomposing a problem

- Breaking down a program into functions is *the fundamental activity* of programming!
- How do you decide when to use a function?
 - One rule: DRY (Don't Repeat Yourself)
 - Whenever you are tempted to copy and paste code, don't!
- Now, how do you design a function?

How to design a function

1. Wishful thinking:

Write the program as if the function already exists

2. Write a specification:

Describe the inputs and output, including their types

No implementation yet!

3. Write tests:

Example inputs and outputs

4. Write the function body (the implementation)

First, write your plan in English, then translate to Python

```
print "Temperature in Fahrenheit:", tempf
tempc = fahr_to_cent(tempf)
print "Temperature in Celsius:", tempc

def fahr_to_cent(f):
    """Input: a number representing degrees Fahrenheit
    Return value: a number representing degrees centigrade
    """
    result = (f - 32) / 9.0 * 5
    return result

assert fahr_to_cent(32) == 0
assert fahr_to_cent(212) == 100
assert fahr_to_cent(98.6) == 37
assert fahr_to_cent(-40) == -40
```

Review: how to evaluate a function call

1. Evaluate the function and its arguments to values
 - If the function value is not a function, execution terminates with an error
2. Create a new stack frame
 - The parent frame is the one where the function is defined
 - In CSE 140, this is always the global frame
 - A frame has bindings from variables to values
 - Looking up a variable starts here
 - Proceeds to the next older frame if no match here
 - The oldest frame is the “global” frame
 - All the frames together are called the “environment”
 - Assignments happen here
3. Assign the actual argument values to the formal parameter variable
 - In the new stack frame
4. Evaluate the body
 - At a return statement, remember the value and exit
 - If at end of the body, return **None**
5. Remove the stack frame
6. The call evaluates to the returned value

Functions are values

The function can be an expression

```
def double(x):  
    return 2*x  
  
print double  
  
myfns = [math.sqrt, int, double, math.cos]  
myfns[1](3.14)  
myfns[2](3.14)  
myfns[3](3.14)
```

```
def doubler():  
    return double  
doubler()(2.718)
```