

List comprehensions (and other shortcuts)

BBM 101 - Introduction to Programming I

Hacettepe University

Fall 2015

Fuat Akal, Aykut Erdem, Erkut Erdem, Vahid Garousi

Three Ways to Define a List

- Explicitly write out the whole thing:

```
squares = [0, 1, 4, 9, 16, 25, 36, 49, 64, 81, 100]
```

- Write a loop to create it:

```
squares = []  
for i in range(11):  
    squares.append(i*i)
```

- Write a list comprehension:

```
squares = [i*i for i in range(11)]
```

- A list comprehension is a concise description of a list
- A list comprehension is shorthand for a loop

Two ways to convert Centigrade to Fahrenheit

```
ctemps = [17.1, 22.3, 18.4, 19.1]
```

With a loop:

```
ftemps = []  
for c in ctemps:  
    f = celsius_to_fahrenheit(c)  
    ftemps.append(f)
```

With a list comprehension:

```
ftemps = [celsius_to_fahrenheit(c) for c in ctemps]
```

The comprehension is usually shorter, more readable, and more efficient

Syntax of a comprehension

```
[ (x,y) for x in seq1 for y in seq2 if sim(x,y) > threshold ]
```

expression

for clause (required)
assigns value to the
variable x

zero or more
additional
for clauses

zero or more **if** clauses

something
that can be
iterated

Semantics of a comprehension

```
[(x,y) for x in seq1 for y in seq2 if sim(x,y) > threshold]
```

```
result = []  
for x in seq1:  
    for y in seq2:  
        if sim(x,y) > threshold:  
            result.append( (x,y) )  
... use result ...
```

Types of comprehensions

List

```
[ i*2 for i in range(3) ]
```

Set

```
{ i*2 for i in range(3) }
```

Dictionary

```
{ key: value for item in sequence ... }
```

```
{ i: i*2 for i in range(3) }
```

Cubes of the first 10 natural numbers

Goal:

Produce: [0, 1, 8, 27, 64, 125, 216, 343, 512, 729]

With a loop:

```
cubes = []  
for x in range(10):  
    cubes.append(x**3)
```

With a list comprehension:

```
cubes = [x**3 for x in range(10)]
```

Powers of 2, 2^0 through 2^{10}

Goal: [1, 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024]

```
[2**i for i in range(11)]
```


Even elements of a list

Goal: Given an input list `nums`, produce a list of the even numbers in `nums`

`nums = [3, 1, 4, 1, 5, 9, 2, 6, 5]`

\Rightarrow `[4, 2, 6]`

`[num for num in nums if num % 2 == 0]`

Dice Rolls

Goal: A list of all possible dice rolls.

With a loop:

```
rolls = []  
for r1 in range(1,7):  
    for r2 in range(1,7):  
        rolls.append( (r1,r2) )
```

With a list comprehension:

```
rolls = [ (r1,r2) for r1 in range(1,7)  
          for r2 in range(1,7) ]
```

All above-average 2-die rolls

Goal: Result list should be a list of 2-tuples:

[(2, 6), (3, 5), (3, 6), (4, 4), (4, 5), (4, 6), (5, 3), (5, 4), (5, 5), (5, 6),
(6, 2), (6, 3), (6, 4), (6, 5), (6, 6)]

```
[ (r1, r2) for r1 in [1,2,3,4,5,6]
      for r2 in [1,2,3,4,5,6]
      if r1 + r2 > 7]
```

OR

```
[ (r1, r2) for r1 in range(1, 7)
      for r2 in range(8-r1, 7) ]
```

All above-average 2-die rolls

Goal: Result list should be a list of 2-tuples:

[(2, 6), (3, 5), (3, 6), (4, 4), (4, 5), (4, 6), (5, 3), (5, 4), (5, 5), (5, 6),
(6, 2), (6, 3), (6, 4), (6, 5), (6, 6)]

```
[(r1, r2) for r1 in [1,2,3,4,5,6]
           for r2 in [1,2,3,4,5,6]
           if r1 + r2 > 7]
```

Remove Duplicates: Use Set Comprehensions

```
{ r1 + r2 for r1 in range(1,7)
  for r2 in range(1,7)
  if r1 + r2 > 7}
```

```
⇒ set([(6, 4), (5, 4), (2, 6), (4, 6), (6, 6), (4, 5),
      (4, 4), (5, 5), (6, 3), (5, 6), (6, 2), (3, 6),
      (5, 3), (6, 5), (3, 5)])
```

Making a Matrix

Goal: A matrix where each element is the sum of its row and column.

With a loop:

```
matrix = []  
for i in range(5):  
    row = []  
    for j in range(5):  
        row.append(i+j)  
    matrix.append(row)
```

With a list comprehension:

```
matrix = [[i+j for j in range(5)] for i in range(5)]
```

More examples

function $4x^2 - 4$

With a loop:

```
num_list = []  
for i in range(-10,11):  
    num_list.append(4*i**2 - 4)
```

With a list comprehension:

```
num_list = [4*i**2 - 4 for i in range(-10,11)]
```

Normalize a list

With a loop:

```
num_list = [6,4,2,8,9,10,3,2,1,3]
total = float(sum(num_list))
for i in range(len(num_list)):
    num_list[i] =
num_list[i]/float(total)
```

With a list comprehension:

```
num_list = [i/total for i in num_list]
```


Matrix of zeros

With a loop:

```
matrix = []  
for i in range(10):  
    matrix.append([0]*10)
```

With a list comprehension:

```
matrix = [[0]*10 for i in range(10)]
```

Multiplication table

With a loop:

```
table = []  
for r in range(1,10):  
    row = []  
    for c in range(1,10):  
        row.append(r*c)  
    table.append(row)
```

With a list comprehension:

```
table = [ [r*c for c in range(1,10)] for r  
in range(1,10)]
```

Mapping of powers of ten

With a loop:

```
powers = {}  
for i in range(-6,7,3):  
    powers[i] = 10**i
```

With a list comprehension:

```
powers = {i:10**i for i in range(-6,7,3)}
```

Dictionary mapping integers to multiples under 100

With a loop:

```
for n in range(1,11):  
    multiples_list = []  
    for i in range(1,101):  
        if i%n == 0:  
            multiples_list.append(i)  
    multiples[n] = multiples_list
```

With a list comprehension:

```
multiples = {n:[i for i in range(1,101) if  
i%n == 0] for n in range(1,11) }
```

A word of caution

List comprehensions are great, but they can get confusing. Error on the side of readability.

```
nums = [n for n in range(100) if  
        sum([int(j) for j in str(n)]) % 7 == 0]
```

```
nums = []  
for n in range(100):  
    digit_sum = sum([int(j) for j in str(n)])  
    if digit_sum % 7 == 0:  
        nums.append(n)
```

A word of caution

List comprehensions are great, but they can get confusing. Error on the side of readability.

```
nums = [n for n in range(100) if  
        sum([int(j) for j in str(n)]) % 7 == 0]
```

```
nums = []  
for n in range(100):  
    digit_sum = sum([int(j) for j in str(n)])  
    if digit_sum % 7 == 0:  
        nums.append(n)
```

A word of caution

List comprehensions are great, but they can get confusing. Error on the side of readability.


```
nums = [n for n in range(100) if  
sum([int(j) for j in str(n)]) % 7 == 0]
```

```
def sum_digits(n):  
    digit_list = [int(i) for i in str(n)]  
    return sum(digit_list)  
nums = [n for n in range(100) if  
        sum_digits(n) % 7 == 0]
```

More shortcuts!

Enumerate a list

```
the_list = [10**i for i in range(10)]  
for i in range(len(the_list)):  
    print str(i) + ': ' + str(the_list[i])
```

A diagram with two blue brackets. The first bracket is under 'i' in 'str(i)' and is labeled 'index' below it. The second bracket is under 'the_list[i]' in 'str(the_list[i])' and is labeled 'value' below it.

Or:

```
for index, value in enumerate(the_list):  
    print str(index) + ': ' + str(value)
```

Like dict.items()

Enumerate a list

Goal: add each element's index itself

```
the_list = range(10)
new_list = []
for i,v in enumerate(the_list):
    new_list.append(i+v)
```

With a list comprehension:

```
the_list = range(10)
new_list = [ i+v for i,v in enumerate(the_list) ]
```

Ternary Assignment

A common pattern in python

```
if x > threshold:  
    flag = True  
else:  
    flag = False
```

Or

```
flag = False  
if x > threshold:  
    flag = True
```

Ternary Assignment

A common pattern in python


```
if x > threshold:  
    flag = True  
else:  
    flag = False
```

```
flag = True if x > threshold else False
```

Ternary Expression
Three elements

Ternary Assignment

`flag = True if x > threshold else False`



Result if true Condition Result if false

- Only works for single expressions as results.
- Only works for if and else (no elif)

Ternary Assignment

Goal: A list of 'odd' or 'even' if that index is odd or even.

```
the_list = []
for i in range(16):
    if i%2 == 0:
        the_list.append('even')
    else:
        the_list.append('odd')
```

or

```
the_list = []
for i in range(16):
    the_list.append('even' if i%2 == 0 else 'odd')
```

Ternary Assignment

Goal: A list of 'odd' or 'even' if that index is odd or even.

```
the_list = []  
for i in range(16):  
    if i%2 == 0:  
        the_list.append('even')  
    else:  
        the_list.append('odd')
```

or

```
the_list = ['even' if i%2 == 0 else 'odd' for i in range(16)]
```

Get more practice

List Comprehensions:

```
[(x,y) for x in seq1 for y in seq2 if  
sim(x,y) > threshold]
```

Enumerate:

```
for index,value in enumerate(seq):  
    ...
```

Ternary If Statement:

```
flag = True if x > threshold else False
```