

# BIL 717

## Image Processing

Apr. 29, 2015

### Graphical Models

Erkut Erdem  
Hacettepe University  
Computer Vision Lab (HUCVL)

### Sample Vision Tasks

- **Image Denoising:** Given a noisy image  $\hat{I}(x,y)$ , where some measurements may be missing, recover the original image  $I(x, y)$ , which is typically assumed to be smooth.
- **Image Segmentation:** Assign labels to pixels in an image, e.g., to segment foreground from background.
- Stereo matching
- Surface Reconstruction
- ...

D. J. Fleet

### Energy Minimization

- Many vision tasks are naturally posed as energy minimization problems on a rectangular grid of pixels:

$$E(u) = E_{data}(u) + E_{smoothness}(u)$$


- The data term  $E_{data}(u)$  expresses our goal that the optimal model  $u$  be consistent with the measurements.
- The smoothness energy  $E_{smoothness}(u)$  is derived from our prior knowledge about plausible solutions.

- Recall Mumford-Shah functional

D. J. Fleet

### Smoothing out cluster assignments


- Assigning a cluster label per pixel may yield outliers:



- How to ensure they are spatially smooth?

K. Grauman

## Solution



P(foreground | image)

Encode dependencies between pixels

$$P(\mathbf{y}; \theta, \text{data}) = \frac{1}{Z} \prod_{i=1..N} f_1(y_i; \theta, \text{data}) \prod_{i,j \in \text{edges}} f_2(y_i, y_j; \theta, \text{data})$$

Labels to be predicted      Individual predictions      Pairwise predictions

Normalizing constant

D. Hoiem

## Writing Likelihood as an “Energy”

$$P(\mathbf{y}; \theta, \text{data}) = \frac{1}{Z} \prod_{i=1..N} p_1(y_i; \theta, \text{data}) \prod_{i,j \in \text{edges}} p_2(y_i, y_j; \theta, \text{data})$$




$$\text{Energy}(\mathbf{y}; \theta, \text{data}) = \sum_i \psi_1(y_i; \theta, \text{data}) + \sum_{i,j \in \text{edges}} \psi_2(y_i, y_j; \theta, \text{data})$$

“Cost” of assignment  $y_i$

“Cost” of pairwise assignment  $y_i, y_j$

D. Hoiem

## Markov Random Fields




Cost to assign a label to each pixel

Cost to assign a pair of labels to connected pixels

$$\text{Energy}(\mathbf{y}; \theta, \text{data}) = \sum_i \psi_1(y_i; \theta, \text{data}) + \sum_{i,j \in \text{edges}} \psi_2(y_i, y_j; \theta, \text{data})$$

D. Hoiem

## Markov Random Fields



- Example: “label smoothing” grid

$$\text{Energy}(\mathbf{y}; \theta, \text{data}) = \sum_i \psi_1(y_i; \theta, \text{data}) + \sum_{i,j \in \text{edges}} \psi_2(y_i, y_j; \theta, \text{data})$$

D. Hoiem

## Binary MRF Example

- Consider the following energy function for two binary random variables,  $y_1$  &  $y_2$ .

	0	1		0	1		0	1
	5	1		0	3		0	3
1	2	3	1	4	0	1	4	0

$$E(y_1, y_2) = \psi_1(y_1) + \psi_2(y_2) + \psi_{12}(y_1, y_2)$$

S. Gould

## Binary MRF Example

- Consider the following energy function for two binary random variables,  $y_1$  &  $y_2$ .

	0	1		0	1		0	1
	5	1		0	3		0	3
1	2	3	1	4	0	1	4	0

$$\begin{aligned}
 E(y_1, y_2) &= \psi_1(y_1) + \psi_2(y_2) + \psi_{12}(y_1, y_2) \\
 &= \underbrace{5\bar{y}_1 + 2y_1}_{\psi_1} \\
 &\quad + \underbrace{\bar{y}_2 + 3y_2}_{\psi_2} \\
 &\quad + \underbrace{3\bar{y}_1y_2 + 4y_1\bar{y}_2}_{\psi_{12}}
 \end{aligned}$$

where  $\bar{y}_1 = 1 - y_1$  and  $\bar{y}_2 = 1 - y_2$ .

S. Gould


## Binary MRF Example

- Consider the following energy function for two binary random variables,  $y_1$  &  $y_2$ .

	0	1		0	1		0	1
	5	1		0	3		0	3
1	2	3	1	4	0	1	4	0

$$\begin{aligned}
 E(y_1, y_2) &= \psi_1(y_1) + \psi_2(y_2) + \psi_{12}(y_1, y_2) \\
 &= \underbrace{5\bar{y}_1 + 2y_1}_{\psi_1} \\
 &\quad + \underbrace{\bar{y}_2 + 3y_2}_{\psi_2} \\
 &\quad + \underbrace{3\bar{y}_1y_2 + 4y_1\bar{y}_2}_{\psi_{12}}
 \end{aligned}$$

where  $\bar{y}_1 = 1 - y_1$  and  $\bar{y}_2 = 1 - y_2$ .



Probability Table

$y_1$	$y_2$	$E$	$P$
0	0	6	0.244
0	1	11	0.002
1	0	7	0.090
1	1	5	0.664

S. Gould

## Image Denoising

- Given a noisy image  $v$ , perhaps with missing pixels, recover an image  $u$  that is both smooth and close to  $v$ .
- Classical techniques:
  - Linear filtering (e.g. Gaussian filtering)
  - Median filtering
  - Wiener filtering
- Modern techniques
  - PDE-based techniques
  - Non-local methods
  - Wavelet techniques
  - MRF-based techniques

Denoising/smoothing techniques that preserve edges in images

## Denoising as a Probabilistic Inference

- Perform maximum a posteriori (MAP) estimation by maximizing the *a posteriori* distribution:

$$p(\text{true image} \mid \text{noisy image}) = p(u \mid v)$$

- By Bayes theorem:  $\frac{\text{likelihood of noisy image given true image}}{\text{image prior}}$

$$p(u|v) = \frac{p(v|u)p(u)}{p(v)} \quad \text{normalization term}$$

- If we take logarithm:

$$\log p(u|v) = \log p(v|u) + \log p(u) - \log p(v)$$

- MAP estimation corresponds to minimizing the encoding cost  $E(u) = -\log p(v|u) - \log p(u)$

$$E(u) = -\log p(v|u) - \log p(u)$$

## Modeling the Likelihood

- We assume that the noise at one pixel is independent of the others.

$$p(v|u) = \prod_{i,j} p(v_{ij} | u_{ij})$$

- We assume that the noise at each pixel is additive and Gaussian distributed:


$$p(v_{ij} | u_{ij}) = G_{\sigma}(v_{ij} - u_{ij})$$

- Thus, we can write the likelihood:

$$p(v|u) = \prod_{i,j} G_{\sigma}(v_{ij} - u_{ij})$$

## Modeling the Prior


- How do we model the prior distribution of true images?
- What does that even mean?
  - We want the prior to describe how probable it is (a-priori) to have a particular true image among the set of all possible images.



S. Roth

## Natural Images

- What distinguishes “natural” images from “fake” ones?




S. Roth



## Simple Observation

- Nearby pixels often have a similar intensity:




- But sometimes there are large intensity changes.

S. Roth

## MRF-based Image Denoising

- Let each pixel be a node in a graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$  with 4-connected neighborhoods.



S. Roth

## Image Denoising

- The energy function is given by

$$E(u) = \sum_{i \in \mathcal{V}} D(u_i) + \sum_{(i,j) \in \mathcal{E}} V(u_i, u_j)$$

- Unary (clique) potentials  $D$  stem from the measurement model, penalizing the discrepancy between the data  $v$  and the solution  $u$ .
- Interaction (clique) potentials  $V$  provide a definition of smoothness, penalizing changes in  $u$  between pixels and their neighbors.

D. J. Fleet

## Denoising as Inference

- Goal:** Find the image  $u$  that minimizes  $E(u)$
- Several options for MAP estimation process:
  - Gradient techniques
  - Gibbs sampling
  - Simulated annealing
  - Belief propagation
  - Graph cut
  - ...

## Quadratic Potentials in 1D

- Let  $v$  be the sum of a smooth 1D signal  $u$  and IID Gaussian noise  $e$ :  
where  $u = (u_1, \dots, u_N)$ ,  $v = (v_1, \dots, v_N)$ , and  $e = (e_1, \dots, e_N)$ .
- With Gaussian IID noise, the negative log likelihood provides a quadratic *data term*. If we let the *smoothness term* be quadratic as well, then up to a constant, the log posterior is

$$E(u) = \sum_{n=1}^N (u_n - v_n)^2 + \lambda \sum_{n=1}^{N-1} (u_{n+1} - u_n)^2$$

D. J. Fleet

## Quadratic Potentials in 1D

- To find the optimal  $u^*$ , we take derivatives of  $E(u)$  with respect to  $u_n$ :

$$\frac{\partial E(u)}{\partial u_n} = 2(u_n - v_n) + 2\lambda(-u_{n-1} + 2u_n - u_{n+1})$$

and therefore the necessary condition for the critical point is

$$u_n + \lambda(-u_{n-1} + 2u_n - u_{n+1}) = v_n$$

- For endpoints we obtain different equations:

$$\begin{aligned} u_1 + \lambda(u_1 - u_2) &= v_1 \\ u_N + \lambda(u_N - u_{N-1}) &= v_N \end{aligned}$$

N linear equations  
in the N unknowns

D. J. Fleet

## Missing Measurements

- Suppose our measurements exist at a subset of positions, denoted  $P$ . Then we can write the energy function as

$$E(u) = \sum_{n \in P} (u_n - v_n)^2 + \lambda \sum_{\text{all } n} (u_{n+1} - u_n)^2$$

- At locations  $n$  where no measurement exists, we have:  $-u_{n-1} + 2u_n - u_{n+1} = 0$
- The Jacobi update equation in this case becomes:

$$u_n^{(t+1)} = \begin{cases} \frac{1}{1+2\lambda} (v_n + \lambda u_{n-1}^{(t)} + \lambda u_{n+1}^{(t)}) & \text{for } n \in P, \\ \frac{1}{2} (u_{n-1}^{(t)} + u_{n+1}^{(t)}) & \text{otherwise} \end{cases}$$

D. J. Fleet

## 2D Image Smoothing

- For 2D images, the analogous energy we want to minimize becomes:

$$\begin{aligned} E(u) &= \sum_{n,m \in P} (u[n, m] - v[n, m])^2 \\ &+ \lambda \sum_{\text{all } n,m} (u[n+1, m] - u[n, m])^2 + (u[n, m+1] - u[n, m])^2 \end{aligned}$$

where  $P$  is a subset of pixels where the measurements  $v$  are available.

Looks familiar??

D. J. Fleet

## Robust Potentials

- Quadratic potentials are not robust to *outliers* and hence they over-smooth edges. These effects will propagate throughout the graph.
- Instead of quadratic potentials, we could use a robust error function  $\rho$ :

$$E(u) = \sum_{n=1}^N \rho(u_n - v_n, \sigma_d) + \lambda \sum_{n=1}^{N-1} \rho(u_{n+1} - u_n, \sigma_s),$$


where  $\sigma_d$  and  $\sigma_s$  are scale parameters.

D. J. Fleet


## Robust Potentials

- Example:** the *Lorentzian* error function

$$\rho(z, \sigma) = \log \left( 1 + \frac{1}{2} \left( \frac{z}{\sigma} \right)^2 \right), \quad \rho'(z, \sigma) = \frac{2z}{2\sigma^2 + z^2}.$$



Error function




Influence function


D. J. Fleet

## Robust Potentials


- Example:** the *Lorentzian* error function
- Smoothing a noisy step edge



Noisy step



LS smoother



Lorentzian smoother

D. J. Fleet

## Robust Image Smoothing

- A Lorentzian smoothness potential encourages an approximately piecewise constant result:



Original image



Output of robust smoothing

D. J. Fleet

## Robust Image Smoothing

- A Lorentzian smoothness potential encourages an approximately piecewise constant result:



Original image



Edges


D. J. Fleet

## Image Segmentation

- Given an image, partition it into meaningful regions or segments.
- Approaches
  - Variational segmentation models
  - Clustering-based approaches (K-means, Mean Shift)
  - Graph-theoretic formulations
- MRF-based techniques

MRFs and Graph-cut

## Markov Random Fields



- Example: “label smoothing” grid

$$\text{Energy}(\mathbf{y}; \theta, \text{data}) = \sum_i \psi_1(y_i; \theta, \text{data}) + \sum_{i,j \in \text{edges}} \psi_2(y_i, y_j; \theta, \text{data})$$

D. Hoiem

## Solving MRFs with graph cuts


### Main idea:

- Construct a graph such that every  $st$ -cut corresponds to a joint assignment to the variables  $\mathbf{y}$
- The cost of the cut should be equal to the energy of the assignment,  $E(\mathbf{y}; \text{data})^*$ .
- The minimum-cut then corresponds to the minimum energy assignment,  $\mathbf{y}^* = \text{argmin}_{\mathbf{y}} E(\mathbf{y}; \text{data})$ .

\* Requires non-negative energies

S. Gould


## Solving MRFs with graph cuts



$$Energy(\mathbf{y}; \theta, data) = \sum_i \psi_1(y_i; \theta, data) + \sum_{i,j \in edges} \psi_2(y_i, y_j; \theta, data)$$

D. Hoiem


## Solving MRFs with graph cuts



$$Energy(\mathbf{y}; \theta, data) = \sum_i \psi_1(y_i; \theta, data) + \sum_{i,j \in edges} \psi_2(y_i, y_j; \theta, data)$$

D. Hoiem

## The *st*-Mincut Problem



### Graph (V, E, C)

Vertices  $V = \{v_1, v_2 \dots v_n\}$


Edges  $E = \{(v_1, v_2) \dots\}$

Costs  $C = \{c_{(1,2)} \dots\}$

P. Kohli

## The *st*-Mincut Problem

What is a *st*-cut?



P. Kohli


## The $st$ -Mincut Problem

What is a  $st$ -cut?

An  $st$ -cut ( $S, T$ ) divides the nodes between source and sink.

What is the cost of a  $st$ -cut?

Sum of cost of all edges going from  $S$  to  $T$



P. Kohli

## The $st$ -Mincut Problem

What is a  $st$ -cut?


An  $st$ -cut ( $S, T$ ) divides the nodes between source and sink.

What is the cost of a  $st$ -cut?

Sum of cost of all edges going from  $S$  to  $T$

What is the  $st$ -mincut?

$st$ -cut with the minimum cost




P. Kohli

## So how does this work?

Construct a graph such that:

1. Any  $st$ -cut corresponds to an assignment of  $x$
2. The cost of the cut is equal to the energy of  $x$  :  $E(x)$



[Hammer, 1965] [Kolmogorov and Zabih, 2002]

P. Kohli

## $st$ -mincut and Energy Minimization

$$E(x) = \sum_i \theta_i(x_i) + \sum_{i,j} \theta_{ij}(x_i, x_j)$$

For all  $ij$   $\theta_{ij}(0,1) + \theta_{ij}(1,0) \geq \theta_{ij}(0,0) + \theta_{ij}(1,1)$

Equivalent (transformable)


$$E(x) = \sum_i c_i x_i + \sum_{i,j} c_{ij} x_i(1-x_j)$$

$$c_{ij} \geq 0$$

P. Kohli

## Graph Construction


$$E(a_1, a_2)$$



P. Kohli

## Graph Construction


$$E(a_1, a_2) = 2a_1$$



P. Kohli

## Graph Construction


$$E(a_1, a_2) = 2a_1 + 5\bar{a}_1$$



P. Kohli

## Graph Construction


$$E(a_1, a_2) = 2a_1 + 5\bar{a}_1 + 9a_2 + 4\bar{a}_2$$



P. Kohli

## Graph Construction


$$E(a_1, a_2) = 2a_1 + 5\bar{a}_1 + 9a_2 + 4\bar{a}_2 + 2a_1\bar{a}_2$$



P. Kohli

## Graph Construction


$$E(a_1, a_2) = 2a_1 + 5\bar{a}_1 + 9a_2 + 4\bar{a}_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$



P. Kohli

## Graph Construction


$$E(a_1, a_2) = 2a_1 + 5\bar{a}_1 + 9a_2 + 4\bar{a}_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$



P. Kohli

## Graph Construction

$$E(a_1, a_2) = 2a_1 + 5\bar{a}_1 + 9a_2 + 4\bar{a}_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$



Cost of cut = 11

$$a_1 = 1 \quad a_2 = 1$$


$$E(1, 1) = 11$$

P. Kohli



## Graph Construction

$$E(a_1, a_2) = 2a_1 + 5\bar{a}_1 + 9a_2 + 4\bar{a}_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$



st-mincut cost = 8

$$a_1 = 1 \quad a_2 = 0$$


$$E(1, 0) = 8$$

P. Kohli

## How to compute the st-mincut?

Solve the dual maximum flow problem

Compute the maximum flow between Source and Sink s.t.



Edges: Flow < Capacity

Nodes: Flow in = Flow out

Min-cut\Max-flow Theorem

In every network, the maximum flow equals the cost of the st-mincut


Assuming non-negative capacity

P. Kohli

## Maxflow Algorithms

Flow = 0

Augmenting Path Based Algorithms




P. Kohli

## Maxflow Algorithms

Flow = 0

Augmenting Path Based Algorithms




1. Find path from source to sink with positive capacity

P. Kohli

## Maxflow Algorithms

Flow = 0 + 2




Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path

P. Kohli

## Maxflow Algorithms

Flow = 2




Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path

P. Kohli

## Maxflow Algorithms

Flow = 2




Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path
3. Repeat until no path can be found

P. Kohli

## Maxflow Algorithms

Flow = 2




Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path
3. Repeat until no path can be found

P. Kohli

## Maxflow Algorithms

Flow = 2 + 4




Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path
3. Repeat until no path can be found

P. Kohli

## Maxflow Algorithms

Flow = 6




Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path
3. Repeat until no path can be found

P. Kohli

## Maxflow Algorithms

Flow = 6




Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path
3. Repeat until no path can be found

P. Kohli

## Maxflow Algorithms

Flow = 6 + 2




Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path
3. Repeat until no path can be found

P. Kohli

## Maxflow Algorithms




### Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path
3. Repeat until no path can be found

P. Kohli

## Maxflow Algorithms




### Augmenting Path Based Algorithms

1. Find path from source to sink with positive capacity
2. Push maximum possible flow through this path
3. Repeat until no path can be found

P. Kohli

## Flow and Reparametrization


$$E(a_1, a_2) = 2a_1 + 5\bar{a}_1 + 9a_2 + 4\bar{a}_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$



P. Kohli

## Flow and Reparametrization

$$E(a_1, a_2) = 2a_1 + 5\bar{a}_1 + 9a_2 + 4\bar{a}_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$




$$\begin{aligned} &2a_1 + 5\bar{a}_1 \\ &= 2(a_1 + \bar{a}_1) + 3\bar{a}_1 \\ &= 2 + 3\bar{a}_1 \end{aligned}$$

P. Kohli

## Flow and Reparametrization

$$E(a_1, a_2) = 2 + 3\bar{a}_1 + 9a_2 + 4\bar{a}_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$




$$\begin{aligned} &2a_1 + 5\bar{a}_1 \\ &= 2(a_1 + \bar{a}_1) + 3\bar{a}_1 \\ &= 2 + 3\bar{a}_1 \end{aligned}$$

P. Kohli

## Flow and Reparametrization

$$E(a_1, a_2) = 2 + 3\bar{a}_1 + 9a_2 + 4\bar{a}_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$




$$\begin{aligned} &9a_2 + 4\bar{a}_2 \\ &= 4(a_2 + \bar{a}_2) + 5\bar{a}_2 \\ &= 4 + 5\bar{a}_2 \end{aligned}$$

P. Kohli

## Flow and Reparametrization

$$E(a_1, a_2) = 2 + 3\bar{a}_1 + 5a_2 + 4 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$




$$\begin{aligned} &9a_2 + 4\bar{a}_2 \\ &= 4(a_2 + \bar{a}_2) + 5\bar{a}_2 \\ &= 4 + 5\bar{a}_2 \end{aligned}$$

P. Kohli

## Flow and Reparametrization


$$E(a_1, a_2) = 6 + 3\bar{a}_1 + 5a_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$



P. Kohli

## Flow and Reparametrization


$$E(a_1, a_2) = 6 + 3\bar{a}_1 + 5a_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$



P. Kohli

## Flow and Reparametrization

$$E(a_1, a_2) = 6 + 3\bar{a}_1 + 5a_2 + 2a_1\bar{a}_2 + \bar{a}_1a_2$$



$$\begin{aligned} &3\bar{a}_1 + 5a_2 + 2a_1\bar{a}_2 \\ &= 2(\bar{a}_1 + a_2 + a_1\bar{a}_2) + \bar{a}_1 + 3a_2 \\ &= 2(1 + \bar{a}_1a_2) + \bar{a}_1 + 3a_2 \end{aligned}$$

$$F_1 = \bar{a}_1 + a_2 + a_1\bar{a}_2$$


$$F_2 = 1 + \bar{a}_1a_2$$

$a_1$	$a_2$	$F_1$	$F_2$
0	0	1	1
0	1	2	2
1	0	1	1
1	1	1	1

P. Kohli

## Flow and Reparametrization

$$E(a_1, a_2) = 8 + \bar{a}_1 + 3a_2 + 3\bar{a}_1a_2$$



$$\begin{aligned} &3\bar{a}_1 + 5a_2 + 2a_1\bar{a}_2 \\ &= 2(\bar{a}_1 + a_2 + a_1\bar{a}_2) + \bar{a}_1 + 3a_2 \\ &= 2(1 + \bar{a}_1a_2) + \bar{a}_1 + 3a_2 \end{aligned}$$

$$F_1 = \bar{a}_1 + a_2 + a_1\bar{a}_2$$


$$F_2 = 1 + \bar{a}_1a_2$$

$a_1$	$a_2$	$F_1$	$F_2$
0	0	1	1
0	1	2	2
1	0	1	1
1	1	1	1

P. Kohli

## Flow and Reparametrization

$$E(a_1, a_2) = 8 + \bar{a}_1 + 3a_2 + 3\bar{a}_1a_2$$



No more  
augmenting paths  
possible


P. Kohli

## Flow and Reparametrization

$$E(a_1, a_2) = \boxed{8} + \boxed{\bar{a}_1 + 3a_2 + 3\bar{a}_1 a_2}$$

Residual Graph  
(positive coefficients)

Total Flow  
bound on the  
optimal solution




Tight Bound >> Inference of the optimal solution becomes trivial  
P. Kohli

## Flow and Reparametrization

$$E(a_1, a_2) = \boxed{8} + \boxed{\bar{a}_1 + 3a_2 + 3\bar{a}_1 a_2}$$

Residual Graph  
(positive coefficients)

Total Flow  
bound on the  
energy of the  
optimal solution



st-mincut cost = 8

$$a_1 = 1 \quad a_2 = 0$$

$$E(1, 0) = 8$$

P. Kohli

## Maxflow in Computer Vision

- Specialized algorithms for vision problems
  - Grid graphs
  - Low connectivity ( $m \sim O(n)$ )
- Dual search tree augmenting path algorithm  
[Boykov and Kolmogorov PAMI 2004]
  - Finds approximate shortest augmenting paths efficiently
  - High worst-case time complexity
  - Empirically outperforms other algorithms on vision problems

P. Kohli

## Code for Image Segmentation

$$E(x) = \sum_i c_i x_i + \sum_{i,j} d_{ij} |x_i - x_j|$$

$$E: \{0, 1\}^n \rightarrow \mathbb{R}$$

$0 \rightarrow fg$   
 $1 \rightarrow bg$

$n$  = number of pixels



Global Minimum ( $x^*$ )

$$x^* = \arg \min_x E(x)$$

How to minimize  $E(x)$ ?

P. Kohli

## How does the code look like?

```
Graph *g;
```

```
For all pixels p
```

```
/* Add a node to the graph */
nodeID(p) = g->add_node();

/* Set cost of terminal edges */
set_weights(nodeID(p), fgCost(p),
            bgCost(p));
```

```
end
```

```
for all adjacent pixels p,q
    add_weights(nodeID(p), nodeID(q),
                cost(p,q));
```

```
end
```

```
g->compute_maxflow();
```

```
label_p = g->is_connected_to_source(nodeID(p));
// is the label of pixel p (0 or 1)
```

Source (0)



Sink (1)



P. Kohli

## How does the code look like?

```
Graph *g;
```

```
For all pixels p
```

```
/* Add a node to the graph */
nodeID(p) = g->add_node();

/* Set cost of terminal edges */
set_weights(nodeID(p), fgCost(p),
            bgCost(p));
```


```
end
```

```
for all adjacent pixels p,q
    add_weights(nodeID(p), nodeID(q),
                cost(p,q));
```

```
end
```

```
g->compute_maxflow();
```

```
label_p = g->is_connected_to_source(nodeID(p));
// is the label of pixel p (0 or 1)
```



P. Kohli

## How does the code look like?

```
Graph *g;
```

```
For all pixels p
```

```
/* Add a node to the graph */
nodeID(p) = g->add_node();

/* Set cost of terminal edges */
set_weights(nodeID(p), fgCost(p),
            bgCost(p));
```


```
end
```

```
for all adjacent pixels p,q
    add_weights(nodeID(p), nodeID(q),
                cost(p,q));
```

```
end
```

```
g->compute_maxflow();
```

```
label_p = g->is_connected_to_source(nodeID(p));
// is the label of pixel p (0 or 1)
```



P. Kohli

## How does the code look like?

```
Graph *g;
```

```
For all pixels p
```

```
/* Add a node to the graph */
nodeID(p) = g->add_node();

/* Set cost of terminal edges */
set_weights(nodeID(p), fgCost(p),
            bgCost(p));
```


```
end
```

```
for all adjacent pixels p,q
    add_weights(nodeID(p), nodeID(q),
                cost(p,q));
```

```
end
```

```
g->compute_maxflow();
```

```
label_p = g->is_connected_to_source(nodeID(p));
// is the label of pixel p (0 or 1)
```




a<sub>1</sub> = bg a<sub>2</sub> = fg

P. Kohli




## Random Fields in Vision



C. Rother

## GrabCut segmentation



User provides rough indication of foreground region.

Goal: Automatically provide a pixel-level segmentation.

D. Hoiem

## MRF with global potential

GrabCut model [Rother et. al. '04]

$$E(x, \theta^F, \theta^B) = \sum_i F_i(\theta^F)x_i + B_i(\theta^B)(1-x_i) + \sum_{i,j \in N} |x_i - x_j|$$

$$F_i = -\log \Pr(z_i | \theta^F)$$


$$B_i = -\log \Pr(z_i | \theta^B)$$



Image z



Output x



$\theta^{F/B}$  Gaussian Mixture models

**Problem:** for unknown  $x, \theta^F, \theta^B$  the optimization is NP-hard! [Vicente et al. '09]

C. Rother


## GrabCut: Iterated Graph Cuts

[Rother et al. Siggraph '04]



$$\min_{\theta^F, \theta^B} E(x, \theta^F, \theta^B)$$

Learning of the colour distributions



$$\min_x E(x, \theta^F, \theta^B)$$

Graph cut to infer segmentation

Most systems with global variables work like that  
e.g. [ObjCut Kumar et. al. '05, PoseCut Bray et al. '06, LayoutCRF Winn et al. '06]

C. Rother

## GrabCut: Iterated Graph Cuts


1. Define graph
  - usually 4-connected or 8-connected
2. Define unary potentials
  - Color histogram or mixture of Gaussians for background and foreground
$$\text{unary\_potential}(x) = -\log \left( \frac{P(c(x); \theta_{\text{foreground}})}{P(c(x); \theta_{\text{background}})} \right)$$
3. Define pairwise potentials
 
$$\text{edge\_potential}(x, y) = k_1 + k_2 \exp \left\{ -\frac{\|c(x) - c(y)\|^2}{2\sigma^2} \right\}$$
4. Apply graph cuts
5. Return to 2, using current labels to compute foreground, background models

D. Hoiem

## GrabCut: Iterated Graph Cuts





Result




Energy after each iteration

C. Rother

## Colour Model




Iterated  
graph cut



C. Rother

## Optimizing over $\theta$ 's help




Input



no iteration  
[Boykov&Jolly '01]



after convergence  
[GrabCut '04]



Input



after convergence  
[GrabCut '04]


C. Rother

What is easy or hard about these cases for graphcut-based segmentation?




D. Hoiem

Easier examples



D. Hoiem

More difficult Examples



D. Hoiem


Semantic Segmentation  
Joint Object recognition & segmentation



$$E(x, \omega) = \sum_i \theta_i(\omega, x_i) + \sum_i \theta_i(x_i) + \sum_i \theta_i(x_i) + \sum_{i,j} \theta_{ij}(x_i, x_j)$$

(color)                      (location)                      (class)                      (edge aware Ising prior)

$x_i \in \{1, \dots, K\}$  for  $K$  object classes




[TextonBoost; Shotton et al, '06]

C. Rother

## Semantic Segmentation

Joint Object recognition & segmentation




[TextonBoost; Shotton et al, '06]

C. Rother

## Semantic Segmentation

Joint Object recognition & segmentation


Good results ...



[TextonBoost; Shotton et al, '06]

C. Rother

## Random Fields in Vision



C. Rother

## Why Higher-order Functions?

In general  $\theta(x_1, x_2, x_3) \neq \theta(x_1, x_2) + \theta(x_1, x_3) + \theta(x_2, x_3)$


Reasons for higher-order RFs:

- Even better image(texture) models:
  - Field-of Expert [FoE, Roth et al. '05]
  - Curvature [Woodford et al. '08]
- Use **global** Priors:
  - Connectivity [Vicente et al. '08, Nowozin et al. '09]
  - Better encoding label statistics [Woodford et al. '09]
  - Convert global variables to global factors [Vicente et al. '09]

C. Rother

## Modeling the Potentials

- Could the potentials (image priors) be learned from natural images?



Field of Experts  
(FoE), S. Roth &  
M. J. Black, CVPR  
2005

## De-noising with Field-of-Experts

[Roth and Black '05, Ishikawa '09]



$$E(X) = \sum_i (z_i - x_i)^2 / 2\sigma^2 + \sum_c \sum_k \alpha_k (1 + 0.5(J_k x_k)^2)$$

Unary likelihood FoE prior



$x_c$  set of  $n \times n$  patches (here  $2 \times 2$ )

$J_k$  set of filters:



non-convex optimization problem

### How to handle continuous labels in discrete MRF?

From [Ishikawa PAMI '09, Roth et al '05]

C. Rother

## De-noising with Field-of-Experts

[Roth and Black '05, Ishikawa '09]



original image



noisy image,  
 $\sigma=20$

PSNR 22.49dB  
SSIM 0.528



denoised using  
gradient ascent

PSNR 27.60dB  
SSIM 0.810

- Very sharp discontinuities. No blurring across boundaries.
- Noise is removed quite well nonetheless.

S. Roth