


## Chapter 2: System Structures



## Chapter 2: System Structures

- Operating System Services
- User Operating System Interface
- System Calls
- Types of System Calls
- System Programs
- Operating System Design and Implementation
- Operating System Structure
- Operating System Debugging
- Operating System Generation
- System Boot



## Objectives

- To describe the services an operating system provides to users, processes, and other systems
- To discuss the various ways of structuring an operating system
- To explain how operating systems are installed and customized and how they boot



## Operating System Services

- Operating systems provide an environment for execution of programs and services to programs and users
- One set of operating-system services provides functions that are helpful to the user:
  - **User interface** - Almost all operating systems have a user interface (UI).
    - ▶ Varies between **Command-Line (CLI)**, **Graphics User Interface (GUI)**, **Batch**
  - **Program execution** - The system must be able to load a program into memory and to run that program, end execution, either normally or abnormally (indicating error)
  - **I/O operations** - A running program may require I/O, which may involve a file or an I/O device
  - **File-system manipulation** - The file system is of particular interest. Programs need to read and write files and directories, create and delete them, search them, list file information, permission management.





## Operating System Services (Cont.)

- **Communications** – Processes may exchange information, on the same computer or between computers over a network
  - ▶ Communications may be via shared memory or through message passing (packets moved by the OS)
- **Error detection** – OS needs to be constantly aware of possible errors
  - ▶ May occur in the CPU and memory hardware, in I/O devices, in user program
  - ▶ For each type of error, OS should take the appropriate action to ensure correct and consistent computing
  - ▶ Debugging facilities can greatly enhance the user's and programmer's abilities to efficiently use the system




## Operating System Services (Cont.)

- Another set of OS functions exists for ensuring the efficient operation of the system itself via resource sharing
  - **Resource allocation** - When multiple users or multiple jobs running concurrently, resources must be allocated to each of them
    - ▶ Many types of resources - Some (such as CPU cycles, main memory, and file storage) may have special allocation code, others (such as I/O devices) may have general request and release code
  - **Accounting** - To keep track of which users use how much and what kinds of computer resources
  - **Protection and security** - The owners of information stored in a multiuser or networked computer system may want to control use of that information, concurrent processes should not interfere with each other
    - ▶ **Protection** involves ensuring that all access to system resources is controlled
    - ▶ **Security** of the system from outsiders requires user authentication, extends to defending external I/O devices from invalid access attempts
    - ▶ If a system is to be protected and secure, precautions must be instituted throughout it. A chain is only as strong as its weakest link.



## A View of Operating System Services



## User Operating System Interface - CLI

- CLI or **command interpreter** allows direct command entry
  - ▶ Sometimes implemented in kernel, sometimes by systems program
  - ▶ Sometimes multiple flavors implemented – **shells**
  - ▶ Primarily fetches a command from user and executes it
    - Sometimes commands built-in, sometimes just names of programs
      - » If the latter, adding new features doesn't require shell modification





## Bourne Shell Command Interpreter

```

PBG-Mac-Pro-~ pbg$ w
15:24 up 58 mins, 2 users, load averages: 1.51 1.54 1.65
USER  TTY  FROM          LOGINP  TDI# WHAT
pbg   console  -          14:34  50  -
pbg   ssm0    -          12:52  -  -

PBG-Mac-Pro-~ pbg$ iostat 5

          disk1          disk0          cpu          load average
KB/s tps MB/s   KB/s tps MB/s   KB/s tps MB/s   us sy id in   sm 15m
 32.75 243 11.30  64.35 14  0.88  39.67  0  0.02 11  5 84 1.51 1.53 1.63
 4.27 308 1.65   0.00  0  0.00   0.00  0  0.00  4  7 94 1.50 1.51 1.56
 4.28 329 1.37   0.00  0  0.00   0.00  0  0.00  5  9 92 1.44 1.51 1.63

nc
PBG-Mac-Pro-~ pbg$ ls
Applications          Music                  WebDC
Applications (Parallels)  Pando Packages       config.log
Desktop                Pictures               getmanrdate.txt
Documents              Public                 mp
Downloads              Sites                  lsof
Library                 Thumbnails             psmake.plt.txt
Movies                 Volumes                prah.txt
PBG-Mac-Pro-~ pbg$ pwd
/Users/pbg
PBG-Mac-Pro-~ pbg$ ping 192.168.1.1
PING 192.168.1.1 (192.168.1.1): 64 data bytes
64 bytes from 192.168.1.1: icmp_seq=0 ttl=64 time=2.257 ms
64 bytes from 192.168.1.1: icmp_seq=1 ttl=64 time=1.262 ms
nc
--- 192.168.1.1 ping statistics ---
 2 packets transmitted, 2 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 1.202/1.760/2.257/0.488 ms
PBG-Mac-Pro-~ pbg$ !

```



Operating System Concepts – 9th Edition

2.9

Silberschatz, Galvin and Gagne ©2013



## User Operating System Interface - GUI

- User-friendly **desktop** metaphor interface
  - Usually mouse, keyboard, and monitor
  - **Icons** represent files, programs, actions, etc
  - Various mouse buttons over objects in the interface cause various actions (provide information, options, execute function, open directory (known as a **folder**))
  - Invented at Xerox PARC
- Many systems now include both CLI and GUI interfaces
  - Microsoft Windows is GUI with CLI “command” shell
  - Apple Mac OS X is “Aqua” GUI interface with UNIX kernel underneath and shells available
  - Unix and Linux have CLI with optional GUI interfaces (CDE, KDE, GNOME)



Operating System Concepts – 9th Edition

2.10

Silberschatz, Galvin and Gagne ©2013



## Touchscreen Interfaces

- Touchscreen devices require new interfaces
  - Mouse not possible or not desired
  - Actions and selection based on gestures
  - Virtual keyboard for text entry




Operating System Concepts – 9th Edition

2.11

Silberschatz, Galvin and Gagne ©2013



## The Mac OS X GUI



Operating System Concepts – 9th Edition

2.12

Silberschatz, Galvin and Gagne ©2013



## System Calls


- Programming interface to the services provided by the OS
- Typically written in a high-level language (C or C++)
- Mostly accessed by programs via a high-level **Application Program Interface (API)** rather than direct system call use
- Three most common APIs are Win32 API for Windows, POSIX API for POSIX-based systems (including virtually all versions of UNIX, Linux, and Mac OS X), and Java API for the Java virtual machine (JVM)
- Why use APIs rather than system calls?

(Note that the system-call names used throughout this text are generic)



## Example of System Calls

- System call sequence to copy the contents of one file to another file



## Example of Standard API

### EXAMPLE OF STANDARD API

As an example of a standard API, consider the `read()` function that is available in UNIX and Linux systems. The API for this function is obtained from the `man` page by invoking the command

`man read`

on the command line. A description of this API appears below:

```

#include <unistd.h>
ssize_t read(int fd, void *buf, size_t count)
  
```

return value      function name      parameters

A program that uses the `read()` function must include the `unistd.h` header file, as this file defines the `ssize_t` and `size_t` data types (among other things). The parameters passed to `read()` are as follows:

- `int fd`—the file descriptor to be read
- `void *buf`—a buffer where the data will be read into
- `size_t count`—the maximum number of bytes to be read into the buffer


On a successful read, the number of bytes read is returned. A return value of 0 indicates end of file. If an error occurs, `read()` returns `-1`.




## System Call Implementation

- Typically, a number associated with each system call
  - **System-call interface** maintains a table indexed according to these numbers
- The system call interface invokes intended system call in OS kernel and returns status of the system call and any return values
- The caller need know nothing about how the system call is implemented
  - Just needs to obey API and understand what OS will do as a result call
  - Most details of OS interface hidden from programmer by API
    - Managed by run-time support library (set of functions built into libraries included with compiler)





- ## System Call Parameter Passing
- Often, more information is required than simply identity of desired system call
    - Exact type and amount of information vary according to OS and call
  - Three general methods used to pass parameters to the OS
    - Simplest: pass the parameters in registers
      - ▶ In some cases, may be more parameters than registers
    - Parameters stored in a block, or table, in memory, and address of block passed as a parameter in a register
      - ▶ This approach taken by Linux and Solaris
    - Parameters placed, or **pushed**, onto the **stack** by the program and **popped** off the stack by the operating system
    - Block and stack methods do not limit the number or length of parameters being passed
- Operating System Concepts – 9th Edition      2.18      Silberschatz, Galvin and Gagne ©2013



- ## Types of System Calls
- Process control
    - end, abort
    - load, execute
    - create process, terminate process
    - get process attributes, set process attributes
    - wait for time
    - wait event, signal event
    - allocate and free memory
  - Dump memory if error
  - **Debugger** for determining **bugs**, **single step** execution
  - **Locks** for managing access to shared data between processes
- Operating System Concepts – 9th Edition      2.20      Silberschatz, Galvin and Gagne ©2013



## Types of System Calls

- File management
  - create file, delete file
  - open, close file
  - read, write, reposition
  - get and set file attributes
  
- Device management
  - request device, release device
  - read, write, reposition
  - get device attributes, set device attributes
  - logically attach or detach devices



## Types of System Calls (Cont.)

- Information maintenance
  - get time or date, set time or date
  - get system data, set system data
  - get and set process, file, or device attributes
  
- Communications
  - create, delete communication connection
  - send, receive messages if **message passing model** to **host name** or **process name**
    - ▶ From **client** to **server**
  - **Shared-memory model** create and gain access to memory regions
  - transfer status information
  - attach and detach remote devices



## Types of System Calls (Cont.)

- Protection
  - Control access to resources
  - Get and set permissions
  - Allow and deny user access



## Examples of Windows and Unix System Calls


	Windows	Unix
Process Control	CreateProcess() ExitProcess() WaitForSingleObject()	fork() exit() wait()
File Manipulation	CreateFile() ReadFile() WriteFile() CloseHandle()	open() read() write() close()
Device Manipulation	SetConsoleMode() ReadConsole() WriteConsole()	ioctl() read() write()
Information Maintenance	GetCurrentProcessID() SetTimer() Sleep()	getpid() alarm() sleep()
Communication	CreatePipe() CreateFileMapping() MapViewOfFile()	pipe() shmget() mmap()
Protection	SetFileSecurity() InitializeSecurityDescriptor() SetSecurityDescriptorGroup()	chmod() umask() chown()





## Standard C Library Example

- C program invoking printf() library call, which calls write() system call



## System Programs

- System programs provide a convenient environment for program development and execution. They can be divided into:
  - File manipulation
  - Status information sometimes stored in a File modification
  - Programming language support
  - Program loading and execution
  - Communications
  - Background services
  - Application programs
- Most users' view of the operation system is defined by system programs, not the actual system calls



## System Programs

- Provide a convenient environment for program development and execution
  - Some of them are simply user interfaces to system calls; others are considerably more complex
- **File management** - Create, delete, copy, rename, print, dump, list, and generally manipulate files and directories
- **Status information**
  - Some ask the system for info - date, time, amount of available memory, disk space, number of users
  - Others provide detailed performance, logging, and debugging information
  - Typically, these programs format and print the output to the terminal or other output devices
  - Some systems implement a **registry** - used to store and retrieve configuration information



## System Programs (Cont.)

- **File modification**
  - Text editors to create and modify files
  - Special commands to search contents of files or perform transformations of the text
- **Programming-language support** - Compilers, assemblers, debuggers and interpreters sometimes provided
- **Program loading and execution**- Absolute loaders, relocatable loaders, linkage editors, and overlay-loaders, debugging systems for higher-level and machine language
- **Communications** - Provide the mechanism for creating virtual connections among processes, users, and computer systems
  - Allow users to send messages to one another' s screens, browse web pages, send electronic-mail messages, log in remotely, transfer files from one machine to another






## System Programs (Cont.)

- **Background Services**
  - Launch at boot time
    - ▶ Some for system startup, then terminate
    - ▶ Some from system boot to shutdown
  - Provide facilities like disk checking, process scheduling, error logging, printing
  - Run in user context not kernel context
  - Known as **services, subsystems, daemons**
- **Application programs**
  - Don't pertain to system
  - Run by users
  - Not typically considered part of OS
  - Launched by command line, mouse click, finger poke



## Example: MS-DOS

- Single-tasking
- Shell invoked when system booted
- Simple method to run program
  - No process created
- Single memory space
- Loads program into memory, overwriting all but the kernel
- Program exit -> shell reloaded




(a) At system startup (b) running a program



## Example: FreeBSD

- Unix variant
- Multitasking
- User login -> invoke user's choice of shell
- Shell executes fork() system call to create process
  - Executes exec() to load program into process
  - Shell waits for process to terminate or continues with user commands
- Process exits with code of 0 – no error or > 0 – error code



## Example: UNIX

- UNIX – limited by hardware functionality, the original UNIX operating system had limited structuring. The UNIX OS consists of two separable parts
  - Systems programs
  - The kernel
    - ▶ Consists of everything below the system-call interface and above the physical hardware
    - ▶ Provides the file system, CPU scheduling, memory management, and other operating-system functions; a large number of functions for one level









## Traditional UNIX System Structure

Beyond simple but not fully layered



## Layered Approach

- The operating system is divided into a number of layers (levels), each built on top of lower layers. The bottom layer (layer 0), is the hardware; the highest (layer N) is the user interface.
- With modularity, layers are selected such that each uses functions (operations) and services of only lower-level layers



## Modules

- Most modern operating systems implement **loadable kernel modules**
  - Uses object-oriented approach
  - Each core component is separate
  - Each talks to the others over known interfaces
  - Each is loadable as needed within the kernel
- Overall, similar to layers but with more flexible
  - Linux, Solaris, etc



## Operating-System Debugging

- **Debugging** is finding and fixing errors, or **bugs**
- OSES generate **log files** containing error information
- Failure of an application can generate **core dump** file capturing memory of the process
- Operating system failure can generate **crash dump** file containing kernel memory
- Beyond crashes, performance tuning can optimize system performance
  - Sometimes using **trace listings** of activities, recorded for analysis
  - **Profiling** is periodic sampling of instruction pointer to look for statistical trends


Kernighan's Law: "Debugging is twice as hard as writing the code in the first place. Therefore, if you write the code as cleverly as possible, you are, by definition, not smart enough to debug it."





## Performance Tuning

- Improve performance by removing bottlenecks
- OS must provide means of computing and displaying measures of system behavior
- For example, "top" program or Windows Task Manager



## System Boot

- When power initialized on system, execution starts at a fixed memory location
  - Firmware ROM used to hold initial boot code
- Operating system must be made available to hardware so hardware can start it
  - Small piece of code – **bootstrap loader**, stored in **ROM** or **EEPROM** locates the kernel, loads it into memory, and starts it
  - Sometimes two-step process where **boot block** at fixed location loaded by ROM code, which loads bootstrap loader from disk
- Common bootstrap loader, **GRUB**, allows selection of kernel from multiple disks, versions, kernel options
- Kernel loads and system is then **running**



## Reading Assignment

- Read the following sections as a reading assignment. You will be responsible from the reading assignments in the exam.
  - Sections 2.1-2.5,
  - Sections 2.7.1-2.7.3
  - Section 2.10

