

List comprehensions (and other shortcuts)

BBM 101 - Introduction to Programming I

Hacettepe University
Fall 2016

Fuat Akal, Aykut Erdem, Erkut Erdem

Slides based on material prepared by Ruth Anderson, Michael Ernst and Bill Howe in the course CSE 140 University of Washington

1

Three Ways to Define a List

- Explicitly write out the whole thing:
`squares = [0, 1, 4, 9, 16, 25, 36, 49, 64, 81, 100]`
- Write a loop to create it:
`squares = []`
`for i in range(11):`
 `squares.append(i*i)`
- Write a **list comprehension**:
`squares = [i*i for i in range(11)]`
- A list comprehension is a concise description of a list
- A list comprehension is shorthand for a loop

2

Two ways to convert Centigrade to Fahrenheit

```
ctemps = [17.1, 22.3, 18.4, 19.1]
```

With a loop:

```
ftemps = []  
for c in ctemps:  
    f = celsius_to_fahrenheit(c)  
    ftemps.append(f)
```

With a list comprehension:

```
ftemps = [celsius_to_fahrenheit(c) for c in ctemps]
```

The comprehension is usually shorter, more readable, and more efficient

3

Syntax of a comprehension

```
[(x,y) for x in seq1 for y in seq2 if sim(x,y) > threshold]
```

expression for clause (required) zero or more additional for clauses zero or more if clauses

assigns value to the variable x

something that can be iterated

4

Semantics of a comprehension

```
[(x,y) for x in seq1 for y in seq2 if sim(x,y) > threshold]
```

```
result = []  
for x in seq1:  
    for y in seq2:  
        if sim(x,y) > threshold:  
            result.append( (x,y) )  
... use result ...
```

5

Types of comprehensions

List

```
[ i*2 for i in range(3) ]
```

Set

```
{ i*2 for i in range(3) }
```

Dictionary

```
{ key: value for item in sequence ... }  
{ i: i*2 for i in range(3) }
```

6

Cubes of the first 10 natural numbers

Goal:

Produce: [0, 1, 8, 27, 64, 125, 216, 343, 512, 729]

With a loop:

```
cubes = []  
for x in range(10):  
    cubes.append(x**3)
```

With a list comprehension:

```
cubes = [x**3 for x in range(10)]
```

7

Powers of 2, 2^0 through 2^{10}

Goal: [1, 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024]

```
[2**i for i in range(11)]
```

8

Even elements of a list

Goal: Given an input list `nums`, produce a list of the even numbers in `nums`

```
nums = [3, 1, 4, 1, 5, 9, 2, 6, 5]
⇒ [4, 2, 6]
[num for num in nums if num % 2 == 0]
```

9

Dice Rolls

Goal: A list of all possible dice rolls.

With a loop:

```
rolls = []
for r1 in range(1,7):
    for r2 in range(1,7):
        rolls.append( (r1,r2) )
```

With a list comprehension:

```
rolls = [ (r1,r2) for r1 in range(1,7)
          for r2 in range(1,7) ]
```

10

All above-average 2-die rolls

Goal: Result list should be a list of 2-tuples:

```
[(2, 6), (3, 5), (3, 6), (4, 4), (4, 5), (4, 6), (5, 3), (5, 4), (5, 5), (5, 6),
(6, 2), (6, 3), (6, 4), (6, 5), (6, 6)]
```

```
[(r1, r2) for r1 in [1,2,3,4,5,6]
           for r2 in [1,2,3,4,5,6]
           if r1 + r2 > 7]
```

OR

```
[(r1, r2) for r1 in range(1, 7)
           for r2 in range(8-r1, 7) ]
```

11

All above-average 2-die rolls

Goal: Result list should be a list of 2-tuples:

```
[(2, 6), (3, 5), (3, 6), (4, 4), (4, 5), (4, 6), (5, 3), (5, 4), (5, 5), (5, 6),
(6, 2), (6, 3), (6, 4), (6, 5), (6, 6)]
```

```
[(r1, r2) for r1 in [1,2,3,4,5,6]
           for r2 in [1,2,3,4,5,6]
           if r1 + r2 > 7]
```

Remove Duplicates: Use Set Comprehensions

```
{ r1 + r2 for r1 in range(1,7)
  for r2 in range(1,7)
  if r1 + r2 > 7 }
⇒ set([(6, 4), (5, 4), (2, 6), (4, 6), (6, 6), (4,
5), (4, 4), (5, 5), (6, 3), (5, 6), (6, 2), (3, 6),
(5, 3), (6, 5), (3, 5)])
```

12

Making a Matrix

Goal: A matrix where each element is the sum of its row and column.

With a loop:

```
matrix = []
for i in range(5):
    row = []
    for j in range(5):
        row.append(i+j)
    matrix.append(row)
```

With a list comprehension:

```
matrix = [[i+j for j in range(5)] for i in range(5)]
```

13

More examples

function $4x^2 - 4$

With a loop:

```
num_list = []
for i in range(-10,11):
    num_list.append(4*i**2 - 4)
```

With a list comprehension:

```
num_list = [4*i**2 - 4 for i in range(-10,11)]
```

15

Normalize a list

```
num_list = [6,4,2,8,9,10,3,2,1,3]
total = float(sum(num_list))
```

With a loop:

```
for i in range(len(num_list)):
    num_list[i] = num_list[i]/float(total)
```

With a list comprehension:

```
num_list = [i/total for i in num_list]
```

16

Matrix of zeros

With a loop:

```
matrix = []
for i in range(10):
    matrix.append([0]*10)
```

With a list comprehension:

```
matrix = [[0]*10 for i in range(10)]
```

17

Multiplication table

With a loop:

```
table = []
for r in range(1,10):
    row = []
    for c in range(1,10):
        row.append(r*c)
    table.append(row)
```

With a list comprehension:

```
table = [ [r*c for c in range(1,10)] for r
in range(1,10) ]
```

18

Mapping of powers of ten

With a loop:

```
powers = {}
for i in range(-6,7,3):
    powers[i] = 10**i
```

With a list comprehension:

```
powers = {i:10**i for i in range(-6,7,3)}
```

19

Dictionary mapping integers to multiples under 100

With a loop:

```
for n in range(1,11):
    multiples_list = []
    for i in range(1,101):
        if i%n == 0:
            multiples_list.append(i)
    multiples[n] = multiples_list
```

With a dictionary comprehension:

```
multiples = {n:[i for i in range(1,101) if
i%n == 0] for n in range(1,11) }
```

20

A word of caution

List comprehensions are great, but they can get confusing.
Error on the side of readability.

```
nums = [n for n in range(100) if
        sum([int(j) for j in str(n)]) % 7 == 0]

nums = []
for n in range(100):
    digit_sum = sum([int(j) for j in str(n)])
    if digit_sum % 7 == 0:
        nums.append(n)
```

21

A word of caution

List comprehensions are great, but they can get confusing.
Error on the side of readability.

```
nums = [n for n in range(100) if
        sum([int(j) for j in str(n)]) % 7 == 0]

def sum_digits(n):
    digit_list = [int(i) for i in str(n)]
    return sum(digit_list)
nums = [n for n in range(100) if
        sum_digits(n) % 7 == 0]
```

22

More shortcuts!

Enumerate a list

```
the_list = [10**i for i in range(10)]
for i in range(len(the_list)):
    print(str(i) + ': ' + str(the_list[i]))
           index
```

Or:

```
for index,value in enumerate(the_list):
    print(str(index) + ': ' + str(value))
```

Like dict.items()

24

Enumerate a list

Goal: add each element's index itself

```
the_list = range(10)
new_list = []
for i,v in enumerate(the_list):
    new_list.append(i+v)
```

With a list comprehension:

```
the_list = range(10)
new_list = [ i+v for i,v in enumerate(the_list) ]
```

25

Ternary Assignment

A common pattern in python

```
if x > threshold:
    flag = True
else:
    flag = False
```

Or

```
flag = False
if x > threshold:
    flag = True
```

26

Ternary Assignment

A common pattern in python

```
if x > threshold:
    flag = True
else:
    flag = False
```

```
flag = True if x > threshold else False
```

Ternary Expression
Three elements

27

Ternary Assignment

```
flag = True if x > threshold else False
```

Result if true Condition Result if false

- Only works for single expressions as results.
- Only works for if and else (no elif)

28

Ternary Assignment

Goal: A list of 'odd' or 'even' if that index is odd or even.

```
the_list = []
for i in range(16):
    if i%2 == 0:
        the_list.append('even')
    else:
        the_list.append('odd')
```

or

```
the_list = []
for i in range(16):
    the_list.append('even' if i%2 == 0 else 'odd')
```

29

Ternary Assignment

Goal: A list of 'odd' or 'even' if that index is odd or even.

```
the_list = []
for i in range(16):
    if i%2 == 0:
        the_list.append('even')
    else:
        the_list.append('odd')
```

or

```
the_list = ['even' if i%2 == 0 else 'odd' for i in range(16)]
```

30

Get more practice

List Comprehensions:

```
[(x,y) for x in seq1 for y in seq2 if
    sim(x,y) > threshold]
```

Enumerate:

```
for index,value in enumerate(seq):
    ...
```

Ternary If Statement:

```
flag = True if x > threshold else False
```

31